

Safety Data Sheet

Manufacturer Name:
14 Eastern Park Rd.
East Hartford, CT 06108

Emergency Tele
Information Telephone No.:
(860) 218-2210

Chemtrec: 800-262-8200

Latest Revision: 08/11/2017

Section I: Product Identification

Product No.: Series 206 LTB
Product Name: INTERIOR EGGSHELL FINISH
Product Class: SATIN FINISH WALL PAINT

Emergency Contact: Chemtrec CCN201349
Contact Phone: 800-424-9300

Section II: Hazardous Identification

Classification

Some of the chemicals included in this formulation are considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)



Signal word: DANGER

Section III: Composition/Ingredients

Ingredient Name	CAS No.	Weight percent	Occupational Exposure Limits	Vapor Pressure mm
Titanium Dioxide	13463-67-7	21.1 %	ACGIH TLV 10mg/m ³ as dust OSHA PEL 10mg/m ³ as dust	N/A

Section IV: First aid measures

EMERGENCY AND FIRST AID PROCEDURES:

EYE: Flush with water. Seek medical attention if irritation persists.

SKIN: Wash with soap and water. Seek medical attention if irritation persists.

INHALATION: Remove victim to fresh air. Seek medical attention.

INGESTION: Do not induce vomiting. Consult a physician. Do not give anything by mouth to an unconscious person. Keep head low so that stomach content doesn't get into lungs.

Section V: Fire Fighting Measures

EXTINGUISHING MEDIA: Foam, Alcohol Foam, Co₂, Dry Chemical, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point. Dry coatings films are capable of burning and giving off oxides of carbon & Nitrogen.

SPECIAL FIRE FIGHTING PROCEDURES: N/A

Section VI: Accidental release measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate all ignition sources. Ventilate area. Keep unauthorized personnel away.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Stop leak if safe to do so. Absorb spill with vermiculite, saw dust, or other inert material. Once dry, material may be landfilled. Dike far ahead of larger spill for later recovery and disposal.

WASTE DISPOSAL METHOD:

Dispose of material in accordance with local, state, and federal regulations.

Section VII: Safe handling and storage

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

KEEP OUT OF REACH OF CHILDREN

Precautions to be taken in Handling and Storage: Avoid subjecting this product to extreme temperature variations and freezing.

Other Precautions:

Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a cool, well-ventilated area.

Section VIII: Exposure controls/Personal protection

Control parameters

Ingredient	CAS No.	Weight percent	Occupational Exposure Limits	Vapor Pressure mm
Titanium Dioxide	13463-67-7	21.1%	ACGIH TLV 10mg/m3 as dust OSHA PEL 10mg/M3 as dust	N/A

Appropriate engineering controls

Respiratory Protection: The dried paint film poses no respiratory hazards. Use appropriate respirator when spraying wet material to avoid breathing spray mist.

Ventilation: Mechanical local exhaust may be required in confined areas.

Protective Gloves: Impervious.

Eye Glasses: Safety Glasses.

Other Protective Equipment: A protective hood, safety glasses and dust mask should be worn when spraying overhead.
The availability of eye washes and safety showers in work areas are recommended.
Close cover after use.

Section IX: Physical and Chemical Properties

Physical state: Viscous liquid
Specific Gravity: 1.402
Percent Solids by Volume: 41.34
Percent Solids by Weight: 58.24
Weight per Gallon: 11.703
Lbs.VOC/Gallon Less Water: 0.72
Flash Point: Non-Flammable or Explosive

Section X: Stability and Reactivity

Stability: Stable
Hazardous polymerization: Will not occur
Hazardous Decomposition Products: Non known
Conditions to avoid: Avoid breathing of wet air born spray mist
Incompatibility (Materials to avoid): Avoid strong oxidizing agents

Section XI: Toxicological information

Information on likely routes of exposure

Product information

Inhalation: spray mist may cause respiratory irritation.
Eye contact: May cause irritation or damage to eyes.
Skin contact: May cause irritation to skin.

Component information

Chemical name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Titanium Dioxide	>5000 mg/kg (rat)	No Systemic effects	>6.82 mg/L air 4h

Section XII: Ecological Information

Eco toxicity

No information available

Persistence and Degradability

No information available

Bioaccumulation

No information available

Other adverse effects

No information available

Section XIII: Disposal Considerations

Disposal methods

Dispose of in accordance with all applicable federal, state, and local regulations

Section XIV: Transportation information

DOT Classification: Not regulated

IMDG: Not regulated

IATA: Not regulated

Section XV: Regulatory information

SARA 313(CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% ELEMENT
13463-67-7	Titanium Dioxide	21.1%	NA

TSCA CERTIFICATION:

All components of this product are either on the TSCA 8(b) Inventory or otherwise exempt from listing.

TSCA: United States Toxic Substance Control Act Section 8(b) Inventory

CALIFORNIA PROPOSITION 65

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section XVI: Other information

Date of preparation: 08/11/2017

Prepared by: FMI Paint and Chemical Hazardous Communications dept.

Rev. 003

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation and verification. Before using any product, read its label.