



## **SERIES 101**

### **“One Coat Ceiling Coater”**

#### **PRODUCT DESCRIPTION:**

“Series 101 One Coat Interior Ceiling Coater” delivers one coat coverage in a self-priming bright white finish. A dead flat paint to mask surface imperfections while achieving outstanding uniformity. A top of the line, very bright white, high quality coating for a variety ceiling surfaces.

#### **RECOMMENDED USES:**

“Series 101 One Coat Interior Ceiling Coater” is designed for sheetrock, plaster, acoustical and concrete ceilings. Not recommended over calcimine. Also recommended as an economical primer on new sheetrock to be top coated with flat wall paint.

#### **PERFORMANCE INFORMATION:**

Excellent flow and leveling. Flat finish to hide surface imperfections. Spatter resistant. One coat coverage. Can be applied by a brush, roller or spray. No primer needed.

#### **CHARACTERISTICS:**

**Vehicle:** Vinyl Acrylic

**Finish:** Flat

**Spread Rate:** On smooth surfaces, app. 300-350 sf/gal. On rough surfaces, app. 250-300 sf/gal. Coverage varies depending on porosity of surfaces and environmental considerations.

**Drying Time:** Dries to touch in 30 minutes. To re-coat, 2 hours.

**Weight:** 11.6 lbs per gal.

**Percent Solids/Volume:** 36%

**Percent Solids/Weight:** 54%

**Viscosity:** 115-120 Ku's

**Recommended Film Thickness:** 6 mils wet, 2.16 mils dry

**Packaging:** 5 gal. container, 2 gal. containers

**Flammability:** Non-Flammable

**VOC's:** 91.60 grams per liter



### **SPECIFICATIONS:**

#### **Surface Preparation:**

Surfaces must be clean and dry.

#### **Previously painted ceilings:**

Remove contaminants. It is strongly recommended that all loose or peeling paint is mechanically sanded and all remaining edges of existing paint be “feathered” to eliminate any sharp profiles. Water stains, smoke stains and any other staining substance with a potential to bleed should be spot primed with a stain killing primer prior to application.

#### **Mildew:**

If it is determined that the surfaces are contaminated with spores, mildew, fungus, etc., remove by scrubbing or power washing surface with a solution of 1 cup heavy duty, abrasive cleaner and 1 quart household bleach dissolved into 3 quarts water. Apply liberally to all affected surfaces. Allow solution to remain on surface until there is visible alteration to biological contaminants. Dark spots should disappear. Flush surface thoroughly with water, allow to dry completely, and then apply “One Coat Interior Ceiling Coater.”

### **Application and Reduction:**

This product has been designed for brush, roll, pad or spray application. Thinning is not recommended. Apply at temperatures above 50F. Protect from freezing.

### **Clean-up Information:**

Clean up equipment and area with detergent and water. Flush spray equipment with mineral spirits after cleaning with water or detergent and water.