



SERIES 205

“Interior Satin Wall and Trim”

PRODUCT DESCRIPTION:

“Series 205 Satin” is a self-priming interior satin enamel suitable for high traffic areas. This satin finish resists dirt and grime and provides excellent hiding and durability. Series 205 produces a finish like an oil based satin enamel.

RECOMMENDED USES:

“Series 205 Satin” is recommended for high traffic areas such kitchens, bathrooms, kids’ rooms, rec rooms, and all wooden trim surfaces. Recommended for walls and trim.

PERFORMANCE INFORMATION:

Primer and finisher in one. Beautiful satin enamel sheen. Can be applied by a brush, roller or spray. Mildew resistant. High hiding. Available in thousands of colors including our ice white.

CHARACTERISTICS:

Vehicle: Vinyl Acrylic

Finish: Satin

Spread Rate: 250-400 sf/gal depending on veracity.

Drying Time: Dries to touch in 1 hour. To re-coat, 2 hours.

Weight: 11.63 lbs per gal.

Percent Solids/Volume: 36.33% + or – 2

Percent Solids/Weight: 54.26% + or – 2

Viscosity: 95-110 Ku’s

Packaging: 5 gal. container, 2 gal. containers

Flammability: Non-Flammable

VOC’s: 138.76 grams per liter



SPECIFICATIONS:

Surface Preparation:

All surfaces should be properly prepared and cleaned. Loose paint should be scraped and sanded to a smooth surface. Wash off dirt and grease with household detergent, rinse and allow to dry. Lightly sand glossy surfaces to a dull finish. Fill any cracks or holes with the appropriate filler, allow to dry and sand to a smooth surface. Remove all dust with a damp cloth. All new stucco, plaster and masonry must be allowed to cure for 30 days prior to painting.

Priming: Series 206 Interior Eggshell Enamel is self-priming. Special primers are not necessary over properly prepared uncoated and previously painted interior surfaces. Water stains, smoke, ink, knots and any other stains that have the potential to bleed through should be primed with an appropriate stain blocking primer.

Mildew:

If it is determined that the surfaces are contaminated with spores, mildew, fungus, etc., remove by scrubbing or power washing surface with a solution of 1 cup heavy duty, abrasive cleaner and 1 quart household bleach dissolved into 3 quarts water. Apply liberally to all affected surfaces. Allow solution to remain on surface until there is visible alteration to biological contaminants. Dark spots should disappear. Flush surface thoroughly with water, allow to dry completely, and then apply "Interior Satin Enamel."

Application and Reduction:

This product has been designed for brush, roll, pad or spray application. Thinning is not recommended. Apply at temperatures above 50F. Protect from freezing.

Clean-up Information:

Clean up equipment and area with detergent and water. Flush spray equipment with mineral spirits after cleaning with water or detergent and water.