

Safety Data Sheet

Manufacturer Name:
FMI PAINT AND CHEMICAL
14 Eastern Park Rd.
East Hartford, CT 06108

Emergency Telephone No.:
Chemtrec: 800-262-8200
Information Telephone No.:
(860) 2218-2210

Last Revision: 8-11-2010

Section I: Product Identification

Product No.: 411 HDCLRUV
Product Name: Water Repellant Heavy Duty Clear UV Blocker
Product Class: Water Repellent Wood Coating

Section II: Hazardous Ingredients

<i>Ingredient</i>	<i>CAS No.</i>	<i>Weight Percent</i>	<i>Occupational Exposure Limits</i>	<i>Vapor pressure mm Hg @ temp.</i>
Mineral Spirits	8052-41-3	49	500ppm	2.9@20C
Solvent in Resin Mixture	64741-65-7	11	300ppm	2.6@20C

Section III: Physical Data

Boiling Range: 212F (water)
Vapor Density: Heavier than air
Evaporation Weight: slower than ether
Solids By Volume: 31.58
Solids By Weight: 37.28
% Volatile By Volume: 68.52
% Volatile By Weight: 62.72
Weight per Gallon: 7.10
VOC's: 4.42 lbs per gal.

Section IV: Fire and Explosion Hazard Data

FLAMMABILITY CLASSIFICATION: Combustible Liquid – Class II
FLASH POINT: 104 F. (Tcc) LEL: 10

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat, sparks, electrical equipment and open flame. Closed containers may explode when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus is recommended. Avoid accumulation of water as product will float.

Section V: Health Hazard Data

EFFECTS OF OVEREXPOSURE:

EYES: Contact may result in eye irritation.

SKIN: Prolonged or repeated contact can cause skin irritation and Dermatitis.

INHALATION: High concentrations, prolonged exposure irritating to mucous membrane.

INGESTION: Liquid ingestion may result in vomiting.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: dermal (all), pulmonary (all),

PRIMARY ROUTE(S) OF ENTRY: Dermal, Inhalation, Ingestion

EMERGENCY AND FIRST AID PROCEDURES:

EYE: Contact may result in eye irritation.

SKIN: Wash with soap and water, remove contaminated clothing. If irritation persists, seek medical attention.

INHALATION: Remove victim to fresh air. Restore breathing. Seek medical advice.

INGESTION: Do not induce vomiting! If vomiting occurs, keep head below hips.

Section VI: Reactivity Data

Stability: stable

Hazardous polymerization: will not occur

Hazardous Decomposition Products: Carbon Monoxide and unidentified organics may be formed during combustion.

Conditions to Avoid: Avoid heat and open flames.

Incompatibility (Materials to Avoid): Avoid oxidizing materials.

Section VII: Spill or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate sources of ignition. Dike spill and soak up with inert material. Keep spill out of surface waters and any watercourses leading to surface waters.

WASTE DISPOSAL METHOD:

Dispose of material in accordance with local, state, and federal regulations.

Section VIII: Safe Handling and Use Information

Respiratory Protection: Organic vapor respirator recommended.

Ventilation: Use explosion-proof exhaust as required to control vapor concentrations.

Protective Gloves: Impervious Gloves recommended

Eye Glasses: Safety Glasses or goggles recommended

Other Protective Equipment: Emergency shower and eye wash facilities recommended

Hygienic Practices:

Section IX: Special Precautions

Precautions to be taken in Handling and Storing: Store away from oxidizing materials in a cool dry place with adequate ventilation. Keep away from heat and open flames. Keep containers tightly sealed.

Other Precautions: Wash with soap and water before eating drinking or smoking. Launder contaminated clothing before reuse.