

Safety Data Sheet

Manufacturer Name:
FMI PAINT AND CHEMICAL
14 Eastern Park Rd.
East Hartford, CT 06108

Emergency Telephone No.:
Chemtec: 800-262-8200
Information Telephone No.:
(860) 218-2210

Last Revision: 8-11-2010

Section I: Product Identification

Product No.: 408
Product Name: Weathercoat 100% Acrylic Low Luster House and Trim Paint
Product Class: 100% Acrylic House and Trim Paint

Section II: Hazardous Ingredients/Sara III Information

<i>Ingredient</i>	<i>CAS No.</i>	<i>Weight Percent</i>	<i>Occupational Exposure Limits</i>	<i>Vapor pressure mm Hg @ temp.</i>
N/A	N/A	N/A	N/A	N/A

Section III: Physical Data

Boiling Range: 212F (water)
Vapor Density: Heavier than air
Evaporation Weight: slower than ether
Solids by Volume: 40.4%
Solids by Weight: 57.4
Weight per Gallon: 11.57
VOC: .39 lbs per gallon

Section IV: Fire and Explosion Hazard Data

FLAMMABILITY CLASSIFICATION: Non-Flammable

FLASH POINT: N/A LEL: 2.6

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog, Other

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point dry coatings films are capable of burning and giving off oxides of Carbon & Nitrogen.

SPECIAL FIRE FIGHTING PROCEDURES: N/A

Section V: Health Hazard Data

EFFECTS OF OVEREXPOSURE:

INHALATION: May cause irritation of the nose, throat, and respiratory tract and symptoms of headache and nausea.

SKIN: Prolonged or repeated contact may cause skin irritation.

EYE: Direct contact with product may cause eye irritation.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Chronic skin rashes or respiratory conditions may be aggravated by exposure.

PRIMARY ROUTE(S) OF ENTRY: Dermal, Inhalation, Ingestion

EMERGENCY AND FIRST AID PROCEDURES:

EYE: Wash with water for 15 minutes consult physician if irritation persists.

SKIN: Wash thoroughly with soap and water.

INHALATION: Remove victim to fresh air.

INGESTION: If victim is conscious, give two glasses of water to drink. Consult a physician. Do not give anything by mouth to an unconscious person.

Section VI: Reactivity Data

Stability: stable

Hazardous polymerization: will not occur

Hazardous Decomposition Products: N/A

Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): N/A

Section VII: Spill or Leak Procedures**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Keep spill out of sewers and pen bodies of water. Dike and contain spill with inert material. Transfer the liquid to containers for recovery or disposal.

WASTE DISPOSAL METHOD:

Dispose of material in accordance with local, state, and federal regulations.

Section VIII: Safe Handling and Use Information

Respiratory Protection: None required if good ventilation is maintained. Other wise use a MESA/NIOSH approved respirator.

Ventilation: Use mechanical, local exhaust system.

Protective Gloves: Impervious

Eye Glasses: Safety Glasses

Other Protective Equipment:

Hygienic Practices:

Section IX: Special Precautions

Precautions to be taken in Handling and Storing: Keep from freezing. If product freezes, it is rendered useless.

Other Precautions: Avoid prolonged breathing of spray vapor.

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation and verification. Before using any product, read its label.