Series 100

INTERIOR LATEX FLAT WALL PAINT

Manufacturer of Paints and Stains
www.fmipaint.com

PRODUCT DESCRIPTION:
SERIES 100 INTERIOR FLAT WALL PAINT" IS A HIGH QUALITY, INTERIOR FLAT ONE COAT LATEX WALL PAINT PROVIDIMG A SMOOTH, BEAUTIFUL, EASY TO WASH COATING WITH EXCELLENT RESISTANCE TO MILDEW AND MOISTURE. SELF-PRIMING AND EASY TO APPLY. AVAILABLE IN THOUSANDS OF COLORS. FLAT FINISH MASKS IRREGULARITIES IN UNEVEN WALL SURFACES.

RECOMMENDED USES:
SERIES 100 INTERIOR FLAT WALL PAINT" CAN BE USED DIRECTLY OVER EXISTING OR BARE DRYWALL OR PLASTER MASONRY AND NON-BLEEDING WOOD. FOR INTERIOR USE ONLY.

PERFORMANCE INFORMATION:
FLAT FINISH. CAN BE APPLIED BY ROLLER, BRUSH OR SPRAY. MILDEW RESISTANT. SELF-PRIMING. ONE COAT HIDING. SUPERIOR FLOW AND LEVEL.

APPLICATION AND REDUCTION INFORMATION:
THIS PRODUCT HAS BEEN DESIGNED FOR BRUSH, ROLL, PAD OR SPRAY APPLICATION. THINNING IS NOT RECOMMENDED. APPLY AT TEMPERATURES ABOVE 50F. PROTECT FROM

CHARACTERISTICS:
VEHICLE: VINYL ACRYLIC
FINISH: FLAT
SPREAD RATE: ON SMOOTH SURFACES, APP. 300-350 SF/GAL. ON ROUGH SURFACES, APP. 200-250 SF/GAL. COVERAGE VARIES DEPENDING ON POROSITY OF SURFACES AND ENVIRONMENTAL CONSIDERATIONS.
DRYING TIME: DRIES TO TOUCH IN 30 MINUTES. TO RE-COAT, 2 HOURS.
WEIGHT: 11.63 LBS PER GAL.
PERCENT SOLIDS/VOLUME: 40.5% + OR – 2
PERCENT SOLIDS/WEIGHT: 57.6% + OR – 2
VISCOSITY: 100-110 KU'S
PACKAGING: 5 GAL. CONTAINER, 2 GAL. CONTAINERS
VOC'S: .41 LBS/GAL.

CLEAN-UP INFORMATION:
CLEAN UP EQUIPMENT AND AREA WITH DETERGENT AND WATER. FLUSH SPRAY EQUIPMENT WITH MINERAL SPIRITS AFTER CLEANING WITH WATER OR DETERGENT AND WATER.

SPECIFICATION

SURFACE PREPARATION:
REMOVE ALL CONTAMINATION BY WASHING WITH AN APPROPRIATE CLEANER AND ALLOW TO DRY. PEELED OR CHECKED PAINT SHOULD BE SCRAPED AND SANDED TO A SMOOTH SURFACE. GLOSSY SURFACES SHOULD BE DULLED. STAINS FROM WATER, SMOKE, INK, PENCIL, OR GREASE SHOULD BE SEALED WITH A STAIN BLOCKING PRIMER.

DRYWALL/PLASTER:
ALL CRACKS AND HOLES SHOULD BE PATCHED WITH SPACKLING COMPOUND AND SANDED SMOOTH. REMOVE ALL SANDING DUST PRIOR TO PAINTING. SELF-PRIME USING TWO COATS OF SERIES 100 INTERIOR FLAT WALL PAINT.

CEMENT, AND BLOCK:
ALL NEW SURFACES MUST BE FULLY CURED. CHECK WITH THE MANUFACTURER FOR RECOMMENDED CURING TIMES. REMOVE ALL FORMS OF CURING AGENTS. ROUGH SURFACES SHOULD BE FILLED TO PROVIDE A SMOOTH SURFACE. SELF-PRIME USING TWO COATS OF SERIES 100 INTERIOR FLAT WALL PAINT.

WOOD:
PREVIOUSLY PAINTED WOOD SHOULD BE SANDED TO A SMOOTH SURFACE. KNOTS OR TANNIN STAINS SHOULD BE PRIMED WITH A STAIN BLOCKING PRIMER. APPLY ONE OR TWO COATS OF SERIES 100 INTERIOR FLAT WALL PAINT AS NECESSARY.

MILDEW:
IF IT IS DETERMINED THAT THE SURFACES ARE CONTAMINATED WITH SPORES, MILDEW, FUNGUS, ETC., REMOVE BY SCRUBBING OR POWER WASHING SURFACE WITH A SOLUTION OF 1 CUP HEAVY DUTY, ABRASIVE CLEANER AND 1 QUART HOUSEHOLD BLEACH DISSOLVED INTO 3 QUARTS WATER. APPLY LIBERALLY TO ALL AFFECTED SURFACES. ALLOW SOLUTION TO REMAIN ON SURFACE UNTIL THERE IS VISIBLE ALTERATION TO BIOLOGICAL CONTAMINANTS. DARK SPOTS SHOULD DISAPPEAR. FLUSH SURFACE THOROUGHLY WITH WATER, ALLOW TO DRY COMPLETELY, AND THEN APPLY "INTERIOR FLAT WALL PAINT."

DISCLAIMER
The information in this data sheet is given to the best of FMI Paint's knowledge and practical experience. Users may consult with FMI Paint on the general suitability of the product for their needs and specific application practices though it remains each user's responsibility to determine the suitability of the product for the user's particular use. The condition of the substrate and application are not within FMI Paint's control. Therefore no implied conditions, warranties or other terms will apply to the Product. FMI Paint does not and cannot warrant the results which the user may obtain by using the product. In no event will FMI Paint be liable to the user for any kind of loss (whether direct or indirect) even if FMI Paint was previously advised of it. In line with FMI Paint's policy for continuous development and improvement, FMI Paint reserves the right to modify the product and the information in this data sheet without prior notice. It is the user's responsibility to check with FMI Paint for the latest version of this data sheet.