Series 101

ONE COAT CEILING COATER AND SHEETROCK PRIMER

Manufacturer of Paints and Stains
www.fmipaint.com

PRODUCT DESCRIPTION:
"SERIES 101 ONE COAT INTERIOR CEILING COATER AND SHEETROCK PRIMER" DELIVERS ONE COAT COVERAGE IN A SELF-PRIMING BRIGHT WHITE FINISH. A DEAD FLAT PAINT TO MASK SURFACE IMPERFECTIONS WHILE ACHIEVING OUTSTANDING UNIFORMITY. A TOP OF THE LINE, VERY BRIGHT WHITE, HIGH QUALITY COATING FOR SHEETROCK, PLASTER, CEILING TILES AND OTHER SURFACES WHERE A FLAT FINISH IS DESIRABLE.

RECOMMENDED USES:
"SERIES 101 ONE COAT INTERIOR CEILING COATER AND SHEETROCK PRIMER" IS DESIGNED FOR SHEETROCK, PLASTER, ACOUSTICAL AND CONCRETE CEILINGS. NOT RECOMMENDED OVER CALCIMINE. ALSO RECOMMENDED AS AN ECONOMICAL, HIGH HIDING PRIMER ON NEW SHEETROCK TO BE TOP COATED WITH FLAT, EGGSHELL, SATIN AND SEMI-GLOSS TOP-COATS.

PERFORMANCE INFORMATION:
EXCELLENT FLOW AND LEVELING. FLAT FINISH TO HIDE SURFACE IMPERFECTIONS. SPATTER RESISTANT. ONE COAT COVERAGE. CAN BE APPLIED BY A BRUSH, ROLLER OR SPRAY. NO SPECIAL PRIMER NEEDED. EXCELLENT TOUCH UP RESULTS.

CHARACTERISTICS:
VEHICLE: VINYL ACRYLIC
FINISH: FLAT
SPREAD RATE: ON SMOOTH SURFACES, APP. 300-350 SF/GAL. ON ROUGH SURFACES, APP. 250-300 SF/GAL. COVERAGE VARIES DEPENDING ON POROSITY OF SURFACES AND ENVIRONMENTAL CONSIDERATIONS.
DRYING TIME: DRIES TO TOUCH IN 30 MINUTES. TO RE-COAT, 2 HOURS.
WEIGHT: 11.7 LBS. PER GAL.
PERCENT SOLIDS/VOLUME: 37.51% + OR – 1%
PERCENT SOLIDS/WEIGHT: 56% + OR – 1%
VISCOSITY: 115-120 KU'S
RECOMMENDED FILM THICKNESS: 6 MILS WET, 2.34 MILS DRY
PACKAGING: 5 GAL. CONTAINER, 2 GAL. CONTAINERS
VOC'S: .80 LBS. PER GAL.

CLEAN-UP INFORMATION:
CLEAN UP EQUIPMENT AND AREA WITH DETERGENT AND WATER. FLUSH SPRAY EQUIPMENT WITH MINERAL SPIRITS AFTER CLEANING WITH WATER OR DETERGENT AND WATER.

APPLICATION AND REDUCTION INFORMATION:
THIS PRODUCT HAS BEEN DESIGNED FOR BRUSH, ROLLER OR SPRAY APPLICATION. THINNING IS NOT RECOMMENDED. APPLY AT TEMPERATURES ABOVE 50F. PROTECT FROM FREEZING.

SPECIFICATION

SURFACE PREPARATION:
SURFACES MUST BE CLEAN AND DRY.

PREVIOUSLY PAINTED CEILINGS, CONCRETE, ACOUSTICAL AND CEILING TILES:
REMOVE CONTAMINANTS. IT IS STRONGLY RECOMMENDED THAT ALL LOOSE OR PEELING PAINT IS MECHANICALLY SANDED AND ALL REMAINING EDGES OF EXISTING PAINT BE "FEATHERED" TO ELIMINATE ANY SHARP PROFILES. WATER STAINS, SMOKE STAINS AND ANY OTHER STAINING SUBSTANCE WITH A POTENTIAL TO BLEED SHOULD BE SPOT PRIMED WITH A STAIN KILLING PRIMER PRIOR TO APPLICATION.

NEW OR BARE SHEETROCK:
NO SPECIAL PRIMER IS RECOMMENDED. WATER STAINS, SMOKE STAINS AND ANY OTHER SUBSTANCE WITH A POTENTIAL TO BLEED THROUGH SHOULD BE SPOT PRIMED WITH A STAIN KILLING PRIMER. APPLY ONE COAT VIA BRUSH, ROLLER OR SPRAY.

MILDEW:
IF IT IS DETERMINED THAT THE SURFACES ARE CONTAMINATED WITH SPORES, MILDEW, FUNGUS, ETC., REMOVE BY SCRUBBING OR POWER WASHING SURFACE WITH A SOLUTION OF 1 CUP HEAVY DUTY, ABRASIVE CLEANER AND 1 QUART HOUSEHOLD BLEACH DISSOLVED INTO 3 QUARTS WATER. APPLY LIBERALLY TO ALL AFFECTED SURFACES. ALLOW SOLUTION TO REMAIN ON SURFACE UNTIL THERE IS VISIBLE ALTERATION TO BIOLOGICAL CONTAMINANTS. DARK SPOTS SHOULD DISAPPEAR. FLUSH SURFACE THOROUGHLY WITH WATER, ALLOW TO DRY COMPLETELY, AND THEN APPLY "ONE COAT INTERIOR CEILING COATER."

DISCLAIMER
The information in this data sheet is given to the best of FMI Paint's knowledge and practical experience. Users may consult with FMI Paint on the general suitability of the product for their needs and specific application practices though it remains each user's responsibility to determine the suitability of the product for the user's particular use. The condition of the substrate and application are not within FMI Paint's control. Therefore no implied conditions, warranties or other terms will apply to the Product. FMI Paint does not and cannot warrant the results which the user may obtain by using the product. In no event will FMI Paint be liable to the user for any kind of loss (whether direct or indirect) even if FMI Paint was previously advised of it. In line with FMI Paint's policy for continuous development and improvement, FMI Paint reserves the right to modify the product and the information in this data sheet without prior notice. It is the user's responsibility to check with FMI Paint for the latest version of this data sheet.